

## Quantitative Methods Boot Camp

### Homework Exercises for Day 1

1. Make an array with the follow values by directly entering it and store it in **x**.  

```
3 4 5
2 1 2
3 2 1
2 3 1
```
2. Do the following:
  - a. Calculate the size of the array **x** from 1
  - b. Use the **size** command to return the number of rows
  - c. Use the **size** command to return the number of columns
  - d. Use the **length** command to return the number of rows
  - e. Use the **length** command to return the number of columns
3. For all these assume that for each letter the x array is as defined after question 1
  - a. Retrieve the value from the 3<sup>rd</sup> row 2<sup>nd</sup> column of **x**.

What will these do?

- b. **x=[x;3]**
- c. **y=[x;1,2,3]**
- d. **x(:,4)=x(:,2);**
- e. **x.\*(1./x)**
- f. **x+2\*x**
- g. **x([4,2])=x(2,3)**

What will these return?

- a. **x(3,5)**
  - b. **x([2,3,1],[2,1])**
  - c. **x(5)**
  - d. **x(5+x(5))**
  - e. **x([x(5), x(2,1)+1],mean([x(4,2),x(end)]))**
  - f. **x(end,end)**
  - g. **x(end)**
  - h. Make a new array y with two copies of x side by side.
  - i. Make a new array y with two copies of x one on top of the other.
4. What do the following code snippets do?
    - a. 1:10
    - b. 1:3:10
    - c. **start=1**  
**step=2**

```
stop=100
length(start:step:stop)
```

5. Start by typing

```
t=(1:100)*pi/25;
```

Now do the following:

- Plot **sin(t)** on the y axis and t on the x axis.
- Add to this plot (i.e. don't overwrite it) **cos(t)** on the y axis in red circles.
- Now add **tan(t)** in green and make the **LineWidth** equal to 2.
- Plot a green line going from the point (0,0) to the point (20,10) .

6. Consider the following code:

```
x=[];
for i=1:2:10
    x(i)=i;
end
```

- How many times will the loop run?
- What will **x** look like when the loop is done?

7. In the following code, what's the chance that A will equal 1? What is x going to look like?

a.

```
A=ceil(rand*100)
if mod(A,10)~=2
    A=1;
else
    A=2;
end
```

b.

```
x=[];
for i=1:10
    for j=1:10
        for k=1:10
            if i>j & j>k | (i==k & i==j)
                x(i,j,k)=1
            elseif mod(i+j+k,10)>9
                x(i,j,k)=2
            else
                x(i,j,k)=-1;
            end
        end
    end
end
```

8. Look up the help on the **while** loop. What does this program do? Think big picture.

```
a=round(rand*100)
p=0;
while (p==0)
    p=1;
    for x=2:a/2
        if mod(a,x)==0
            p=0;
        end
    end
    a=a+1;
end
a-1
```

9. In a single line of code, create **a**, a 10 by 10 array where all values are zero except along the diagonal where all values equal 5. (Hint: use the eye function (look this up with the MATLAB help)).
10. Starting with the **a** array you just created, and using a *single* line of code: to each element of the sixth row and eighth row of the array **a**, add double the value of the element in the sixth row, six column of array **a**.
11. Use the same array **a** from problems 9 and 10:
- Save a new array **b1** as the array **a** to the power of the value in the fourth row, fifth column of array **a**.
  - Save a new array **b2** as each element of the array **a** to the power of the value in the fourth row, fifth column of array **a**.
12. Using the array from the last 3 problems:
- What is the average value of each column of array **a**? (Try using the built-in MATLAB function)
  - What is the average value of each row of array **a**?
  - What is the average value of every third column (1<sup>st</sup>, 4<sup>th</sup>, 7<sup>th</sup>, etc.) of the array **a**?
  - What is the average value of every other row (1<sup>st</sup>, 3<sup>rd</sup>, 5<sup>th</sup>, etc.) of the array **a**?

*Last updated 8/18/11 by JW.*